

Technical Data

SPC - CORE COLLECTION



SPC - CORE COLLECTION/30

Covering type in accordance with EN ISO 16511:2014	Semirigid multilayer modular floor covering (MMF) with wear resistant top layer
Number of colours	13 Planks / 4 Tiles
Pack. Unit/Pallet	1220x180 mm: 2.20 m ² /88 m ² 906x448 mm: 2.44 m ² /73.20 m ²
Performance classification EN ISO 10582 / ISO 10874	23, 31
Total thickness ISO 24346	5.0 mm
Wear layer thickness ISO 24340	0.3 mm
Surface treatment	yes/PU
Bevelled edges	yes
Total weight ISO 23997	8.375 kg/m ²
Residual indentation ISO 24343-1	≤ 0.1 mm*
Dimensional stability ISO 23999	≤ 0.05 %*
Castor chair suitability ISO 4918	yes – using EN 12529, Type W
Underfloor heating EN 1264-2	suitable up to 28°C
Behaviour to fire EN 13501-1	Bfl-s1
Resistance to thermal conductivity ISO 8302 / EN 12667	0.02 m ² K/W
Electrical propensity when walked upon EN 1815	< 2 kV
Impact sound improvement ISO 10140-3	20 dB
Colour fastness to artificial light ISO 105-B02/02	≥ 6
Tensile strength of fixings prEN ISO 10582, appendix D	long side ≥ 4.5 kN/m, short side ≥ 5.5 kN/m
Electrostatic characteristics EN 1081	> 10 ¹²
Chemical resistance ISO 26987	conforms**
Slip resistance	R10
Maintenance/Cleaning recommendations:	Dr. Schutz

* Averaged value

(Date: 01.04.2021)

** Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions.

