

Technical specifications

Construction Structure - Structuur - Konstruktion		1/12° Pattern Perfect®
Pile fibre composition Composition des fibres - Poolmateriaal - Material der Polnutschicht		ECONYL® 100% regenerated solution dyed nylon
Secondary backing Envers - Rug - Beschichtung		EcoFlex™ One (94% recycled felt)
Total weight Poids total - Totaal gewicht - Gesamtgewicht		+/- 3650 g/m²
Pile weight Poids du velours - Poolgewicht - Poleinsatzgewicht		+/- 780 g/m²
Surface pile weight Poids du velours utile - Effectieve poolmassa - Polnutschichtgewicht		+/- 410 g/m²
Total thickness Epaisseur totale - Totale dikte - Gesamtdicke		+/- 8,4 mm
Surface pile thickness Hauteur du velours - Poolhoogte - Poldicke		+/- 3,1 mm
Surface pile density Densité du velours - Pooldichtheid - Polrohdichte		+/- 0,133 g/cm³
Number of tufts Nombre de boucles - Aantal noppen - Noppenzahl		181.300/m²
Wear classification Classement d'usage - Gebruiksklasse - Beanspruchungsklasse	EN 1307	33 / LC2
Castor chair suitability Résistance aux chaises à roulettes - Rolstoelgeschiktheid - Stuhllolleneignung	EN 985	A: intensive use
Fire classification Comportement au feu - Brandgedrag - Brandklasse	EN 13501-1	Bfl-s1
Dimensional stability Stabilité dimensionnelle - Dimensionele stabiliteit - Dimensionsstabilität	EN 986	≤ 0,2%
Colour fastness to light Solidité des couleurs à la lumière - Lichtbestendigheid van de kleuren - Lichtechtheit	EN ISO 105-B02	≥ 7
Rubbing fastness Solidité au frottement - Wrijfechtheid - Reibechtheit	EN ISO 105-X12	≥ 4
Colour fastness to water Solidité à l'eau - Waterechtheid - Wasserechtheit	EN ISO 105-E01	≥ 4
Thermal resistance Résistance thermique - Warmtedoorlaatweerstand - Wärmedurchlasswiderstand		ISO 8302 0,121 m².K/W
Sound absorption Absorption phonique - Geluidsabsorptie - Schallabsorptionsgrad		EN ISO 354 0,25 αw Hz 125 250 500 1000 2000 4000 αs 0,00 0,03 0,43 0,20 0,28 0,39
Impact sound reduction Réduction phonique aux bruits d'impacts - Reductie contactgeluid - Trittschallverbesserungsmaß		EN ISO 10140-3 ΔLw = 25 dB
Permanent antistatic Antistatique permanent - Permanent antistatisch - Permanent antistatisch		ISO 6356 ≤ 2 kV
Number of colours Nombre de coloris - Aantal kleuren - Anzahl der Farben		10
Size & Packaging Dimensions & Emballage - Formaat en verpakking - Abmessungen & Verpackung		25 x 100 cm 4 m²/box - 24 boxes/pallet
GUT-Prodis Number Numéro GUT Prodis - Nummer GUT Prodis - GUT-Prodis Nummer		Ongoing







We reserve all rights for technical improvements. 05/2025

